



# WALL MOUNTED DC INVERTER SPLIT SYSTEMS

ECO SERIES



# DC INVERTER ECO SERIES

ECO is a modern and stylish design air conditioner that matches any interior décor.

Swing mode moves flaps up and down for perfect temperature distribution throughout the room.

The operating mode is conveniently displayed on the appliance's LED screen.



LED display



Turbo mode



Timer



Two-directional  
airflow



Washable filter



Dehumidification  
function



Protective coating



Air freshening filter



Auto-restart function



Low noise airflow  
system



Cleanable panel

| SET MODEL                                            | AWI/AWO-26HPDC1D | AWI/AWO-35HPDC1D |
|------------------------------------------------------|------------------|------------------|
| Cooling capacity, W                                  | 2900(1000-3000)  | 3500(1200-3800)  |
| Heating capacity, W                                  | 2900(900-3200)   | 3600(1000-4100)  |
| Power input (cooling), W                             | 1065(170-1350)   | 1280(170-1680)   |
| Power input (heating), W                             | 900(200-1300)    | 1120(200-1650)   |
| Max input current, A                                 | 8,7              | 8,7              |
| Cooling efficiency (SEER)                            | 5,8              | 5,6              |
| Heating efficiency (SCOP)                            | 4,0              | 4,0              |
| Energy class (cooling/heating)                       | A+/A+            | A+/A+            |
| Indoor unit air flow volume, m³/h                    | 430/375/300      | 560/490/395      |
| Indoor unit sound pressure (L <sub>p</sub> ), dB(A)  | 40/35/27         | 40/36/28         |
| Indoor unit dimensions, mm                           | 715×250×188      | 800×275×188      |
| Indoor unit weight, kg                               | 6,5              | 7,4              |
| Outdoor unit sound pressure (L <sub>p</sub> ), dB(A) | 54               | 54               |
| Outdoor unit dimensions, mm                          | 780×540×250      | 780×540×250      |
| Outdoor unit weight, kg                              | 26,2             | 26,9             |
| Refrigerant                                          | R410A            | R410A            |
| Maximum refrigerant pipe length, m                   | 25               | 25               |
| Maximum height difference, m                         | 10               | 10               |
| Working conditions (cooling), °C                     | 0 - +50          | 0 - +50          |
| Working conditions (heating), °C                     | -15 - +30        | -15 - +30        |